Certificate Number UL-CA-L350613-24-52013102-1

Report Reference E350613-20131025

Date 11-Dec-2020

Issued to: Bridgelux Inc

46430 Fremont Blvd Fremont, CA

United States 94538

This is to certify that representative samples of

OOQL8 - Light-emitting-diode Packages Certified for

Canada - Component

See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete

in certain constructional features or restricted in

performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety: CAN/CSA C22.2 NO. 250.13-17, 3rd Ed., Issue Date: 2017-

10-01

Additional Information: See the UL Online Certifications Directory at

https://ig.ulprospector.com for additional information

This *Certificate of Compliance* does not provide authorization to apply the UL Recognized Component Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.






Certificate Number UL-CA-L350613-24-52013102-1

Report Reference E350613-20131025

Date 11-Dec-2020

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
BXRE, BXRE-AB CDEFG-H-IJ, Where	LED Packages
BXRE, designates product family	AZII. AZII. AZII. AZII. AZI
AB, designates the nominal ANSI color temperature	
C, designates minimum CRI	
DEFG, designates model type where the first three	Na Va Va Va Va V
suffixes are as follows and G can be any alphanumeric	3(U) 3(U) 3(U) 3(U) 3(U)
character 10KG, V29 Series, 65FG, V22 Series, 40FG,	
V18 Series, 30FG, V15 Series, 20FG, V13 Series, 10FG,	
V10 Series, 08FG, V8 Series, 06FG – V6 Series	Mil. Mil. Mil. Mil. Mi
H, designates array configuration	. 八 当し八 当し八 当し八 当し八 !
IJ, designates CCT bin options, where i is 0, or 2 for	
Generation 6, i is 7 for Generation 7, and i is 8 for	
Generation 8	WULWULWULWULW





Certificate Number UL-US-L350613-14-52013102-1

Report Reference E350613-20131025

Date 11-Dec-2020

Issued to: Bridgelux Inc

46430 Fremont Blvd Fremont, CA

United States 94538

This is to certify that representative samples of

OOQL2 - Light-emitting-diode Packages - Component

See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete

in certain constructional features or restricted in

performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety: UL 8750, 2nd Ed., Issue Date: 2015-09-15, Revision Date:

2020-09-11

Additional Information: See the UL Online Certifications Directory at

https://iq.ulprospector.com for additional information

This *Certificate of Compliance* does not provide authorization to apply the UL Recognized Component Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.





Certificate Number UL-US-L350613-14-52013102-1

Report Reference E350613-20131025

Date 11-Dec-2020

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
BXRE, BXRE-AB CDEFG-H-IJ, Where	LED Packages
BXRE, designates product family	AZII. AZII. AZII. AZII. AZI
AB, designates the nominal ANSI color temperature	
C, designates minimum CRI	
DEFG, designates model type where the first three	Na Va Va Va Va V
suffixes are as follows and G can be any alphanumeric	3(U) 3(U) 3(U) 3(U) 3(U)
character 10KG, V29 Series, 65FG, V22 Series, 40FG,	
V18 Series, 30FG, V15 Series, 20FG, V13 Series, 10FG,	
V10 Series, 08FG, V8 Series, 06FG – V6 Series	Mil. Mil. Mil. Mil. Mi
H, designates array configuration	. 八 当し八 当し八 当し八 当し八 !
IJ, designates CCT bin options, where i is 0, or 2 for	
Generation 6, i is 7 for Generation 7, and i is 8 for	
Generation 8	WULWULWULWULW

