Certificate Number Report Reference Date	UL-US-L357031-14-70500202-2 E357031-20200507 16-Oct-2020
Issued to:	Bridgelux Inc 46430 Fremont Blvd Fremont, CA United States 94538
This is to certify that representative samples of	OOQA2 - Light-emitting-diode Arrays - Component See Addendum Page for Product Designation(s).
	Have been investigated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.
Standard(s) for Safety:	UL 8750, 2nd Ed., Issue Date: 2015-09-15, Revision Date: 2020-09-11
Additional Information:	See the UL Online Certifications Directory at https://iq.ulprospector.com for additional information

This *Certificate of Compliance* does not provide authorization to apply the UL Recognized Component Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.

Bamely

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Certificate Number Report Reference Date UL-US-L357031-14-70500202-2 E357031-20200507 16-Oct-2020

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
BXRV, BXRV-ab-cdefg-hijk-l-mn-Sx, where: ab, can be TR for tunable white models, or DR for dim to warm models cdef, any alpha numeric characters designating the nominal ANSI color temperature range g, any alpha numeric designating minimum CRI hi, any alpha numeric characters 06, 10. 20. 30. 40. 65, or 1K designating LES diameter jk, any alpha numeric characters designating lumens form factor I, any alpha numeric designating electrical configuration m, any alpha numeric designating CCT bin options SE, suffix designating mechanical variants of PWB holder with connectors where x is any alphanumeric character.	LED modules

Bampleg

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Certificate Number Report Reference Date

UL-CA-L357031-34-70500202-2 E357031-20200507 16-Oct-2020

Issued to: Bridgelux Inc 46430 Fremont Blvd Fremont, CA United States 94538

This is to certify that representative samples of OOQA8 - Light-emitting-diode Arrays Certified for Canada -Component

See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety:	CSA C22.2 NO. 250.13, 4th Ed., Issue Date: 2020-04-01
Additional Information:	See the UL Online Certifications Directory at https://iq.ulprospector.com for additional information

This *Certificate of Compliance* does not provide authorization to apply the UL Recognized Component Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.

Bruce Mahrenholz, Director North American Certification Progra

UL LLC

Certificate Number Report Reference Date UL-CA-L357031-34-70500202-2 E357031-20200507 16-Oct-2020

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
BXRV, BXRV-ab-cdefg-hijk-I-mn-Sx, where: ab, can be TR for tunable white models, or DR for dim to warm models cdef, any alpha numeric characters designating the nominal ANSI color temperature range g, any alpha numeric designating minimum CRI hi, any alpha numeric characters 06, 10. 20. 30. 40. 65, or 1K designating LES diameter jk, any alpha numeric characters designating lumens	LED modules
form factor I, any alpha numeric designating electrical configuration m, any alpha numeric designating product generation n, any alpha numeric designating CCT bin options SE, suffix designating mechanical variants of PWB holder with connectors where x is any alphanumeric character.	

Bamples

Bruce Mahrenholz, Director North American Certification Program

UL LLC