

Ray Files of Bridgelux V10 BXRE-XXX100X-B-7X Products

FTP links to ray files for Bridgelux V10 BXRE-XXX100X-B-7X Array products can be found in this document. In order to download the ray files, please click on the link.

Note:

- The files are based on test of a 3000K 80CRI part at nominal drive current 270mA at 50°C case temperature.
- Customers designing on other color SKUs or at other drive or thermal conditions can use these ray files and adjust the LOP level accordingly in their design software.
- o All the ray files are generated with 1M rays (IES and EUL format have 10M rays).
- All the rays are generated on a plane at z=0, which is at the center of the top surface of light emitting area. For details about where z=0 is aligned, please refer to the two photos at the end of this file, or read radiant source model in ProSource (under alignment tab).
- Please refer to the 3D CAD files of V10 BXRE-XXX100X-B-7X from Bridgelux website for mechanical details of the product.

Radiant Source Model with color information

BXRE-XXX100X-B-7X(Radiant Imaging Source)

Tris-Color:

BXRE-XXX100X-B-7X(Generic ASCII Format)

BXRE-XXX100X-B-7X(Generic Binary Format)

BXRE-XXX100X-B-7X(LightTools Binary Format)

Photopic:

BXRE-XXX100X-B-7X(ASAP Format)

BXRE-XXX100X-B-7X(ASCII Format)

BXRE-XXX100X-B-7X(FRED Format)

BXRE-XXX100X-B-7X(Generic Binary Format)

BXRE-XXX100X-B-7X(LighTools Format)

BXRE-XXX100X-B-7X(LucidShape Format)

BXRE-XXX100X-B-7X(OptiCAD Format)

BXRE-XXX100X-B-7X(Optis Format)

BXRE-XXX100X-B-7X(Photopia Format)

BXRE-XXX100X-B-7X(SIMULUX Format)

BXRE-XXX100X-B-7X(SPECTER Format)

BXRE-XXX100X-B-7X(TracePro)

BXRE-XXX100X-B-7X(Zemax Format)



EUL and IES files:

BXRE-XXX100X-B-7X(EULUMDAT Format)
BXRE-XXX100X-B-7X(IES Format)

Alignment during radiant source model and ray file generation







