

# SMD Products

## Bridgelux Differentiation

- 25+ years of driving LED industry transformation
- Vertical integration across chip, phosphor and package
- Broad product portfolio including CSPs, SMDs, COBs and modules
- Human centric and dynamic lighting technology leader

## Features

- High efficacy and lumens per dollar
- Industry standard form factors and footprints
- 3, 4, and 5 SDCM binning options
- Excellent lumen maintenance
- Thrive™ LEDs closely match natural sunlight, delivering exceptional color quality and supporting human-centric lighting
- F90™ LEDs deliver CRI 90 color quality with equal or better efficacy than traditional CRI 80 LEDs, enabling easy drop-in upgrades



## Indoor Lighting -SMD 5050

Product	CRI	PN	CCT Range	If (mA)	Vf (V)	Power (W)	Flux (lm)	LPW	DS #
5050 (BXEP-)	94	181-24B	2700-6500	45	22	1	152	154	<a href="#">DS76</a>
	90	181-24B	2700-6500	45	22	1	159	160	<a href="#">DS76</a>
		1C5-36C	2700-6500	125	35.2	4.4	539	123	<a href="#">DS299</a>
		435-09C	2700-6500	500	8.9	4.5	604	135	<a href="#">DS298</a>
		425-06C	2700 - 6500	750	6.2	5	640	138	<a href="#">DS909</a>
		425-06CZ	1800-6500		6.2	4.6	577	126	<a href="#">DS676</a>
	80	181-24B	2700-6500	45	22	1	175	177	<a href="#">DS76</a>
		1C5-36C	2700-6500	125	35.2	4.4	636	145	<a href="#">DS299</a>
		185-24CZ	1800-6500	160	24.4	3.9	647	166	<a href="#">DS677</a>
		185-24C	2700-6500		24.4	3.9	615	158	<a href="#">DS911</a>
		322-06DEF	2200-6500	350	5.5	1.9	410	213	<a href="#">DS2501</a>
		322-06EEF	2200-6500		5.5	1.9	410	213	<a href="#">DS2502</a>
		435-09C	2700-6500	500	8.9	5	677	152	<a href="#">DS298</a>
		425-06C	2200 - 6500	750	6.2	5	757	163	<a href="#">DS909</a>
		425-06A	2700-6500		6.3	4.6	722	153	<a href="#">DS219</a>
		425-06A	2700-6500		6.3	4.7	708	150	<a href="#">DS219-1</a>
	425-06CZ	1800-6500	6.2		4.6	683	149	<a href="#">DS676</a>	

All measurements are at T<sub>sp</sub>=25°C. Performance listed for 4000K CCT. Additional electrical configurations and product options are available, please consult your Bridgelux sales representative

© 2026 Bridgelux, Inc. Product specifications are subject to change without notice. Bridgelux and the Bridgelux stylized logo design are registered trademarks of Bridgelux, Inc. All other trademarks are the property of their respective owners.



## Benefits

- Competitive system performance and cost
- Ease of design and rapid go-to-market
- Uniform and consistent white light
- Highly reliable fixture quality

## Applications

- Healthcare
- Residential
- Landscape
- Roadway
- Building Exterior
- Office & Education
- Retail & Hospitality
- Industrial & Warehouse
- Area & Parking Lot



# SMD Products

## Indoor Lighting -SMD 3030, 3535, 4014

Product	CRI	PN	CCT Range	If (mA)	Vf (V)	Power (W)	Flux (lm)	LPW	DS #	
3030 (BXEM-)	90	11L-3DF	2700-6500	65	2.7	0.2	35	199	<a href="#">DS1709</a>	
		21M-3CW	3000	150	2.85	0.4	70	163.7	<a href="#">DS900</a>	
		22H-6D	2700-6500		5.8	1	127	146	<a href="#">DS904</a>	
		12H-6C	2000- 6500		6.1	0.9	124	136	<a href="#">DS297</a>	
		22H-6G	2200-6500	300	5.8	1.8	220	125	<a href="#">DS934</a>	
	80	11L-3DF	2700-6500	65	65	2.7	0.2	41	234	<a href="#">DS1706</a>
		11L-3BF	2700-6500			2.7	0.2	39.5	224	<a href="#">DS1722</a>
		11L-3CF	2700-6500			2.74	0.18	39.5	222	<a href="#">DS1708</a>
		11L-3CFA	2200-6500			2.74	0.18	39.5	222	<a href="#">DS1726</a>
		21L-3FZ	2700-6500			2.72	0.2	37	209	<a href="#">DS948</a>
		21L-3F1Z	2700-6800			2.72	0.2	36	204	<a href="#">DS938</a>
		21L-3CH	2700-6500			2.72	0.2	35.5	201	<a href="#">DS654</a>
		13H-9CS	2700-6500	100	8.9	0.9	154	173	<a href="#">DS656</a>	
		22H-6D	2700 - 6500	150	5.8	1	140	162	<a href="#">DS904</a>	
		12H-6C	2200 - 6500		6.1	0.9	144	158	<a href="#">DS297</a>	
		22H-6G	2200-6500	300	6	1.8	259	148	<a href="#">DS934</a>	
3535 (BXEX-)	95	11H-3B1	2700 - 6500	700	2.88	2	286	142	<a href="#">DS895</a>	
		11H-3A1	2700 - 6500		3	2.1	234	112	<a href="#">DS891</a>	
	90	11H-3B1	2700 - 6500	700	2.88	2	330	164	<a href="#">DS894</a>	
		11H-3A1	2700 - 6500		3	2.1	257	122	<a href="#">DS890</a>	
	80	11H-3B1	2700 - 6500	700	2.88	2	370	184	<a href="#">DS893</a>	
		11H-3A1	2700 - 6500		3	2.1	316	150	<a href="#">DS889</a>	
4014 (BXEW-)	90	11L-3C	2700-6500	60	2.85	0.2	26.5	155	<a href="#">DS239</a>	
		11L-3B	3000-6500		2.9	0.2	27	155	<a href="#">DS217</a>	
	80	11L-3D	4000	60	2.8	0.2	33	196	<a href="#">DS915</a>	
		11L-3D	3000		2.8	0.2	31	185	<a href="#">DS915</a>	
		11L-3C	2700-6500		2.85	0.2	30.5	178	<a href="#">DS239</a>	
		11L-3B	3000-6500		2.9	0.2	30.8	177	<a href="#">DS217</a>	
		11M-3CS	2800		100	2.95	0.3	39.4	134	<a href="#">DS217</a>

All measurements are at T<sub>sp</sub> = 25°C. Performance listed for 4000K CCT. Additional electrical configurations and product options are available, please consult your Bridgelux sales representative

# SMD Products

## Indoor Lighting -SMD 2835 CRI90

Product	CRI	PN	CCT Range	If (mA)	Vf (V)	Power (W)	Flux (lm)	LPW	DS #
SMD 2835 (BXEN-)	90	12H-36A	2500-6500	25	36	1	113	126	<a href="#">DS252</a>
		12H-18A	2700-6500	50	18.1	1	120	133	<a href="#">DS253</a>
		11L-3S	2200-6500	60	2.95	0.2	23	131	<a href="#">DS277</a>
		21L-3FA	1800-6500	65	2.72	0.2	31.9	180	<a href="#">DS1537</a>
		21L-3C4L	2700-6500		2.74	0.2	31	174	<a href="#">DS270-4</a>
		21L-3DHS	2700-6500		2.74	0.2	31	174	<a href="#">DS520-3 (coating)</a>
		21L-3CX	2700-6500		2.74	0.2	30.5	171	<a href="#">DS555-3</a>
		21L-3CS	1800-6500		2.74	0.2	30.5	171	<a href="#">DS555-7 (coating)</a>
		14H-12B	2700-6500	75	12	1	114	127	<a href="#">DS204</a>
		13H-9D	2700-7500	100	8.85	0.9	128	145	<a href="#">DS267-2</a>
		13H-9CN	2600-6500		9.2	0.9	122	133	<a href="#">DS234-1</a>
		13H-9C	2600-6500		9.2	0.9	114	124	<a href="#">DS207</a>
		21M-3D	2700-6500	150	2.85	0.5	69	161	<a href="#">DS246-1</a>
		21M-3C	1800-6500		2.92	0.4	66.3	151	<a href="#">DS544</a>
		21M-3CS	2700-6500		2.92	0.4	66.3	151	<a href="#">DS544-2 (coating)</a>
		21M-3AS	2700-6500		2.95	0.4	64.2	145	<a href="#">DS533</a>
		11M-3C	1800-7500		3	0.5	65	144	<a href="#">DS242</a>
		11M-3S	2200-6500		3.22	0.5	57	118	<a href="#">DS275</a>

All measurements are at T<sub>sp</sub> = 25°C. Performance listed for 4000K CCT. Additional electrical configurations and product options are available, please consult your Bridgelux sales representative

# SMD Products

## Indoor Lighting -SMD 2835 CRI80

Product	CRI	PN	CCT Range	If (mA)	Vf (V)	Power (W)	Flux (lm)	LPW	DS #
<b>SMD 2835 (BXEN-)</b>	80	13H-54A	2700-6500	17	53	0.9	135	150	<a href="#">DS254</a>
		21U-3C	2700-6500	20	2.64	0.1	12.1	229	<a href="#">DS989</a>
		21U-3F	2700-6500		2.64	0.05	12.8	242	<a href="#">DS1471</a>
		14H-36D	2700-6500	25	33.6	0.8	158	188	<a href="#">DS552</a>
		21L-3C6	2700-6500	42	2.7	0.2	26.1	220	<a href="#">DS980</a>
		22H-18D	2300-6700	50	16.8	0.8	158	188	<a href="#">DS551</a>
		21L-3C4	2700-6500	60	2.71	0.2	35.3	217	<a href="#">DS270</a>
		21L-3FL	2700-6500	65	2.7	0.2	39.1	223	<a href="#">DS987-10</a>
		21L-3F	2700-6500		2.71	0.2	38.7	220	<a href="#">DS987</a>
		21L-3FS	2700-6500		2.71	0.2	38.3	217	<a href="#">DS987-11 (coating)</a>
		21L-3DA	2200-6500		2.72	0.2	37.5	212	<a href="#">DS520</a>
		21L-3FA	1800-6500		2.72	0.2	37.5	212	<a href="#">DS1537</a>
		21L-3CS	1800-6500		2.74	0.2	35.5	199	<a href="#">DS555-7 (coating)</a>
		14H-12B	2700-6500	75	12	1	130	144	<a href="#">DS204</a>
		12M-6C	2700-6500	80	5.7	0.5	86.5	190	<a href="#">DS265</a>
		13H-9FL	2700-6500	100	8.75	0.9	165	189	<a href="#">DS1112</a>
		13H-9F	2300-6500		8.8	0.9	162	185	<a href="#">DS545</a>
		12M-6A	2700-6500		6.3	0.6	87	138	<a href="#">DS206</a>
		21M-3DA	2700-6500	150	2.85	0.5	81	189	<a href="#">DS246</a>
		21M-3C	1800-6500		2.92	0.4	78	178	<a href="#">DS544</a>
21M-3CS	2700-6500	2.92	0.4		78	178	<a href="#">DS544-2 (coating)</a>		
12H-6B	2700-6500	6.2	0.9		143.5	154	<a href="#">DS554</a>		

All measurements are at  $T_{sp}=25^{\circ}\text{C}$ . Performance listed for 4000K CCT. Additional electrical configurations and product options are available, please consult your Bridgelux sales representative

# SMD Products

## Bridgelux Thrive™ and F90™ -SMD 2835, 3030, 5050

Product	CRI	PN	CCT Range	If (mA)	Vf (V)	Power (W)	Flux (lm)	LPW	DS #
<b>2835 (BXEN-)</b>	Thrive 90	11L-3C	2700-6500	60	2.9	0.2	26.5	152	<a href="#">DS534</a>
	Thrive 97	11L-3C	2700-6500		2.9	0.2	24	138	<a href="#">DS311</a>
	Thrive 90	13H-9C	2700-6500	100	9.2	0.9	122	133	<a href="#">DS313</a>
	Thrive 97	13H-9C	2700-7400		9.1	0.9	103	114	<a href="#">DS310</a>
	Thrive 97	11M-3C	2700-6500	150	3.1	0.5	56	119	<a href="#">DS312</a>
<b>3030 (BXEM-)</b>	Thrive 95	13H-9D	6500	150	9.3	1.4	160	115	<a href="#">DS658</a>
	Thrive 95	13H-9D	2700		9.3	1.4	135	97	<a href="#">DS658</a>
<b>3030 (BXFM-)</b>	F90	11L-3DF	2700-6500	65	2.7	0.2	39.5	225	<a href="#">DS1707</a>
		21L-3C	2700-6500		2.72	0.2	35.4	200	<a href="#">DS651</a>
		21L-3CZ	2700-6500		2.72	0.2	35.2	199	<a href="#">DS652</a>
	150	12H-6C	2700-6500	6.15	0.9	141	153	<a href="#">DS660</a>	
		12H-6CZ	2700-6500	6.15	0.9	140.3	152	<a href="#">DS659</a>	
<b>2835 (BXFN-)</b>	F80	21L-3C5	2700-6500	42	2.7	0.1	25.3	223	<a href="#">DS528</a>
	50	22H-18D	2300-7000	50	16.8	0.8	150	179	<a href="#">DS547</a>
		21H-18C	2700-6500		18	0.9	140	156	<a href="#">DS508</a>
	65	21L-3FL	2700-6500	65	2.7	0.2	37	210	<a href="#">DS1480</a>
		21L-3C4S	2700-6500		2.7	0.2	35.6	201	<a href="#">DS503-6</a>
		21L-3C4	2700-6500		2.7	0.2	35	198	<a href="#">DS503</a>
		21L-3C3	2700-6500		2.75	0.2	34	190	<a href="#">DS517</a>
		11L-3C3	2700-6500		2.8	0.2	33.7	184	<a href="#">DS502</a>
		11L-3A	2700-7800		2.9	0.2	33.5	179	<a href="#">DS501</a>
		13H-9F	2200-6700		8.8	0.9	141	164	<a href="#">DS507</a>
		13H-9FL	2700-6700		8.8	0.9	162	185	<a href="#">DS1113</a>
	100	13H-9RC	2700-6500	100	8.9	0.9	145	164	<a href="#">DS510</a>
		13H-9D	2200-6800		9	0.9	141.5	158	<a href="#">DS506</a>
		13H-9C	2700-6500		9.2	0.9	127	139	<a href="#">DS505</a>
		13H-98	2700-6800		9.3	0.9	125	134	<a href="#">DS504</a>
		12H-6RC	2700-6500		150	6.1	0.9	144	157

All measurements are at T<sub>sp</sub> = 25°C. Performance listed for 4000K CCT. Additional electrical configurations and product options are available, please consult your Bridgelux sales representative

© 2026 Bridgelux, Inc. Product specifications are subject to change without notice. Bridgelux and the Bridgelux stylized logo design are registered trademarks of Bridgelux, Inc. All other trademarks are the property of their respective owners.

For more information:  
[bridgelux.com](http://bridgelux.com)  
[bridgelux.com/products/smd-products](http://bridgelux.com/products/smd-products)

# SMD Products

## Outdoor Lighting -SMD 2835, 3030, 3535, 5050 & One Blue LED

Product	CRI	PN	CCT Range	If (mA)	Vf (V)	Power (W)	Flux (lm)	LPW	DS #
<b>2835 (BXEN-)</b>	70	21M-3DA	2700-6500	150	2.9	0.4	86	201	<a href="#">DS246-2</a>
<b>3030 (BXEM-)</b>	70	11L-3DF	2700-6500	65	2.7	0.2	41.5	236	<a href="#">DS1705</a>
		13H-9C	2200-6500	100	8.9	0.9	160	180	<a href="#">DS657</a>
		22H-6D	2700 - 6500	150	5.8	0.9	151	175	<a href="#">DS904</a>
		12H-6C	2200 - 6500		6.1	0.9	150	164	<a href="#">DS297</a>
		22H-6G	2200-6500	300	5.8	1.8	282	161	<a href="#">DS934</a>
<b>3535 (BXEX-)</b>	70	11H-3B1	2700 - 6500	700	2.9	2	412	204	<a href="#">DS892</a>
		11H-3B	2200 - 6500		2.93	2.05	408	199	<a href="#">DS1730</a>
		11H-3A1	2700 - 6500		3	2.1	373	178	<a href="#">DS882</a>
<b>5050 (BXEP-)</b>	70	181-24B	2700-6500	45	22	1	206	208	<a href="#">DS76</a>
		1C5-36C	2700-6500	125	35.2	4.4	706	165	<a href="#">DS299</a>
		185-24C	1800-6500	160	24.4	3.9	702	180	<a href="#">DS677</a>
		185-24C	2700-6500		24.4	3.9	666	171	<a href="#">DS911</a>
		322-06DEF	2200-6500	350	5.5	1.9	442	230	<a href="#">DS2501</a>
		322-06EEF	2200-6500		5.5	1.9	442	230	<a href="#">DS2502</a>
		435-09C	2700-6500	500	8.9	4.5	791	177	<a href="#">DS298</a>
		11H-3B	2200-6500	700	2.9	2.1	400	195	<a href="#">DS1730</a>
		425-06C	2200 - 6500	750	6.2	5	818	176	<a href="#">DS909</a>
		425-06A	2700-6500		6.3	4.6	780	166	<a href="#">DS219</a>
		425-06CZ	1800-6500		6.2	4.7	810	174	<a href="#">DS676</a>
<b>2835 (BXEN-)</b>	/	1M-3A	Blue	150	3.2	0.5	13	26.9	<a href="#">DS285</a>

All measurements are at  $T_{\text{sp}}=25^{\circ}\text{C}$ . Performance listed for 4000K CCT. Additional electrical configurations and product options are available, please consult your Bridgelux sales representative